

FULL INVERTER HEAT PUMP

ENERGY
EFFICIENT

Swim All Year Round

with full inverter heating & cooling technology



8 Top Discharge Models

8 Side Discharge Models

Neptune
for swimming pools

X-PRO

SCAN FOR
MORE INFO



KEY FEATURES FOR ALL MODELS

- ✓ Full inverter technology saves you money and power, by intelligently adjusting its power consumption while maintaining your chosen requirements
- ✓ 2 - 3 times more efficient than standard heat pumps
- ✓ TurboSilence® inverter technology for super quiet operation
- ✓ 2-in-1 heating and cooling system
- ✓ Titanium heat exchanger
- ✓ Wi-Fi with smart functions
- ✓ Intuitive display with real-time power consumption data
- ✓ Marine grade anti-corrosion aluminium alloy casing
- ✓ 8 side discharge and 8 top discharge models
- ✓ Compatible with Neptune Heat Pump Controllers

OPERATING CONDITIONS

Specification		Range
Operating Range	Ambient Air Temperature	-15°C – 43°C
Temperature Setting	Heating Capacity	18°C – 40°C
	Cooling Capacity	12°C – 30°C

Neptune X-Pro Heat Pumps feature a revolutionary 2-in-1 heating and cooling system. Designed with a focus on energy efficiency, the X-Pro range offers a quiet, durable and easy to use solution ideal for those who prioritise reliability and efficiency.

Experience total control with a real-time power consumption display and an intuitive interface offering customisable settings and data at your fingertips. Seamlessly connect to Wi-Fi for smart functionality, making comfort management effortless.



TECHNICAL DATA - SIDE DISCHARGE

Model	NHX10	NHX13	NHX17	NHX21	NHX26	NHX32	NHX323	NHX403
Advised Pool Volume (L)	20,000-40,000	25,000-50,000	30,000-60,000	40,000-75,000	55,000-100,000	65,000-120,000	65,000-120,000	90,000-160,000
Heating Capacity (kW) [^]	10.2	13.2	16.8	21.0	25.5	31.5	31.5	40.0
Power Supply	Single Phase, 230V, 50Hz						3 Phase, 400V, 50Hz	
Net Dimension LxWxH (mm)	799x432x650	893x432x650	939x432x650	995x432x750	1125x429x952	1074x539x947	1074x539x947	1260x539x947
Net Weight (kg)	51	61	65	70	98	102	111	126

TECHNICAL DATA - TOP DISCHARGE

Model	NHX10TD	NHX13TD	NHX17TD	NHX21TD	NHX26TD	NHX32TD	NHX32TD3	NHX40TD3
Advised Pool Volume (L)	20,000-40,000	25,000-50,000	30,000-60,000	40,000-75,000	50,000-100,000	65,000-120,000	65,000-120,000	90,000-160,000
Heating Capacity (kW) [^]	10.2	13.2	17.2	21.0	26.0	31.5	31.5	40.0
Power Supply	Single Phase, 230V, 50Hz						3 Phase, 400V, 50Hz	
Net Dimension LxWxH (mm)	710x753x668	710x753x668	710x775x668	710x775x668	710x775x743	729x955x917	729x955x917	845x955x917
Net Weight (kg)	61	66	71	78	102	110	117	141



AVAILABLE FROM YOUR
LOCAL POOL PRO STOCKIST



[^]In Turbo Mode, 26°C air & water temp & 80% humidity.
^{*}Warranty conditions apply.

PUMPS | FILTERS | CHLORINATORS | CLEANERS | UNDERWATER LIGHTS | HEATING | ACCESSORIES | CHEMICALS | SPA PRODUCTS | SPARE PARTS



Simply A Better Choice

Phone Free Call: 1800 143 788 International Phone: + 61 7 3209 7884
Email: office@poolpro.com.au Web: www.poolpro.com.au